

# QuietBox Power Package



## Description

Power Package is utilized to provide filtered power within the QuietBox without degrading RF Shielding Effectiveness

## Features

- 5A 120 VAC Power Package ( includes 10' cord, internal duplex receptacles)
- 15A 120 VAC Power Package ( includes 10' cord, internal duplex receptacle )



## Specification

<b>Voltage drop:</b>	2% maximum at full rated unity power factor load
<b>Current overload:</b>	140%maximum current rating for 15 minutes maximum
<b>Dielectric withstand voltage:</b>	2X rated voltage
<b>Insulation resistance:</b>	As per MIL-F-15733
<b>Insertion Loss:</b>	100dB minimum from 14KHz to 10GHz when measured to MIL-STD-220-A
<b>10' Cord:</b>	3 Conductor 12 Ga. Cab tire, standard 3 prong plug Standard North American power bar with 4 receptacles
<b>Option:</b>	European 240 Volt power bar with 4 receptacles

### 5A 120 VAC Power Package

- 2 x 5 Amp Signal Filter
- 120 VAC/DC voltage
- 0-60Hz frequency
- 9" (L) x 3.5" (W) x 2.5" (H)

### 15A 120 VAC Power Package

- 2 x 15 Amp Signal Filter
- 120 VAC/DC voltage
- 0-60Hz frequency
- 20..1" (L) x 7.1" (W) x 4.14" (H)